## MATERIAL SAFETY DATA SHEET

SECTION 1-PRODUCT AND COMPANY IDENTIFICATION						
PRODUCT NAME: Royal Gloss Enamel Polyurethan	ne Porch & Floor M	lidtone Base				
Product Code Identification Number: 245A320 MSDS Number:						
GENERAL USE: Protective Coating				Paint		
PRODUCT DESCRIPTION: Solvent base alkyd coating, hydrocarbon odor						
MANUFACTURER'S NAME DATE PREPARED: October 2				27 2005	<u> </u>	
Ace Hardware Paint Division		SUPERSEDES: November 20, 2004 Page 1 of 4				
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION				
21901 South Central Avenue		(800) 311-8324				
(CITY, STATE AND ZIP CODE) Matteson, IL 60443-2800	COUNTRY USA	EMERGENCY TELEPHONE NUMBER Infotrac (800) 535-5053 Outside USA (352) 323-3500				
DISTRIBUTOR'S NAME	UUA	illiotrac (c	00/303-3033 Out	SIGE OUT (332) 32	23-3300	
Ace Hardware Corporation						
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION				
2200 Kensington Court			(800) 311-8324  EMERGENCY TELEPHONE NUMBER			
(CITY, STATE AND ZIP CODE) Oak Brook, IL 60523-2100	COUNTRY USA	Infotrac (800) 535-5053 Outside USA (352) 323-3500				
	V. 2 ~ HAZARDOUS INGREDIENTS					
SECTION 2 THAZARDOGS INGREDIENTS    WIGHER OF SHAPEL   ACGINTWA   SARA   RQ						
HAZARDOUS COMPONENTS	CAS#	(by weight)			TITLE III LBS	
Planeter of ables of the state	64740 47.0	1 (7 5 7	PPM MG/M3	PPM MG/M3		
Petroleum distillate, aliphatic	64742-47-8		100 525			
Petroleum distillate, aliphatic	64742-88-7	10 - 30	500 2000			
				· · · · · · · · · · · · · · · · · · ·		
			···			
(a) The exposure limits of this product, when allowed to enter the environment as dust particulate, are covered under the rules of 29 CFR 1910.1000, Table Z						
3, "All inert or nuisance dusts, whether mineral, inorganic or organic."						
	· ·					
SECTION 3 - HAZARDS IDENTIFICATION						
EMERGENCY OVERVIEW						
White liquid, potentially hazardous vapors. Flammable as defined by DOT and TDG for Air / Ocean transport. Classified by DOT as						
Combustible for ground transport in containers less than 120 gallons. Classified as Combustible by OSHA. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death						
in poorly ventilated areas. Hazard symbols for this product - Xn; Risk Phrases - R 10, 20/22, 36/38						
POTENTIAL LIEALTH PERFOYS		_				
POTENTIAL HEALTH EFFECTS INHALATION: High concentrations are irritating to the	o receimten, tract	may cause b	andacho dizzinoce	paucea vemiting a	and malaise	
THE TION. Tight concentrations are inliating to the	ie respiratory tract	, may cause in	sauache, dizziness,	nausea, vomining e	illa Illalaise.	
SKIN: Brief contact may cause slight irritation; prolo	nged contact may	cause modera	te irritation or derma	ıtitis.		
EYES: High vapor concentration or contact may cau	se irritation and di	scomfort				
	oo milaayn alla al	oodiiiletti				
				1		
INGESTION: May result in vomiting; aspiration of vo					e amounts	
aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.						
CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS	No OSHA	REGULATED? No	
OF STORT OF STORY	NIE	140	IANG MUNUGRAPHS:	HO USHA	PEROPHEDI INO	